

## SKATELITE PRO PROPERTIES



This riding surface is a manufactured phenolic saturated wood fiber laminate ramp surface. Skatelite can have up to 10% of recycled content in the material. Skatelite is sensitive about the environment and takes measures to reduce its impact on the planet. In particular Skatelite Pro is an eco-friendly material made primarily of paper from certified managed forests in the U.S. Between 98-99.3% of the Volatile Organic Compounds (VOCs) involved in the Skatelite manufacturing process are captured and destroyed.

Electrical Properties Dielectric Strength Dielectric Constant Dissipation	150 9.24 0.29
Thermal Properties Coeff. Of Thermal Expansion (X Dir) Coeff. Of Thermal Expansion (Y Dir) Coeff. Of Thermal Expansion (Z Dir) Thermal Conductivity 0.00051 cal cr	) 12.8 min/in 45.9/73.5min/in
Water Absorption By Weight	2.15%
Tensile Strength X Direction Y Direction	19,200 psi 13,100 psi
Compressive Strength X Direction Strain @ Failure Y Direction Strain @ Failure Z Direction Strain @ Failure	18,400 psi 7.09% 15,900 psi 7.15% 30,000 psi ~20%
Flexural Strength (Face in Tension) X Direction Y Direction	22,000 psi 17,300 psi

phone 877-489-3539 – fax 626-330-5803 – www.spohnranch.com – info@spohnranch.com 15131B Clark Ave. City of Industry, CA 91745





Flexural Strength (Edge in Tension) X Direction Y Direction	20,400 psi 16,100 psi
Shore Hardness	22
Face Edge	90 88
Izod Impact (Face Impact)	
X Direction Y Direction	2.48 ft. lb. Per 1.46 in. of width
Izod Impact (Edge Impact)	
X Direction	0.68 ft. lb. Per
Y Direction	0.62 in. of width
Burning Rate Aging	Very Slow Improves Mechanical and Electrical Properties
Sunlight	Darkens Surface

Rainier Richlite Company 624 East 15<sup>th</sup> St. Tacoma, WA 98421 888-383-5533



## SKATELITE PRO MATERIAL SAFETY DATA SHEET



#### **Section 1: Ingredients**

Chemical Family: Cured Phenol-formaldehyde

**Product Use:** Various within modeling and pattern making industries. **Hazard Statement:** This material safety data sheet (MSDS) has been prepared in compliance with the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product in not considered to be a hazardous chemical under that standard.

#### Section 2: Physical Data

Appearance: Tan, odorless flat sheets Percent Volatile: 0 (zero) Insoluble in water Specific Gravity: 1.24

#### Section 3: Fire and Explosion Data

**Extinguishing media:** Self-extinguishing; remove source of heat. **Special fire fighting procedures:** Use self-contained breathing apparatus. **Unusual fire and explosion data:** Combustion products may be toxic.

#### Section 4: Reactivity Data

#### Stability: Stable

**Conditions to Avoid:** Excessive Heat for prolonged periods. **Incompatibility:** Very strong alkali

Hazardous Decomposition Products: Combustion may form toxic materials. Oxides of carbon and nitrogen, benzene, toluene, methane, phenol, formaldehyde. Hazardous Polymerization: Will not occur.

#### Section 5: Health Hazard Data

**Primary Routes of Exposure:** Eye, dermal, ingestion or inhalation of dust from abraded material.

Threshold Limit Value: Not hazardous

**Overexposure effects:** Completely cross-linked phenol-formaldehyde resin is inert and non-toxic.

**Eye Contact:** Dust that contacts the eye may be irritating or cause mechanical injury.

Skin Contact: May cause slight skin irritation.

**Ingestion:** It is reasonable to anticipate ingestion of the dust would be irritating to the GI tract.





**Inhalation:** Dust may be irritating to the respiratory tract and cause coughing or sneezing.

#### **Section 6: First Aid Measures**

**Eyes:** Immediately flush eyes with water for at least 15 minutes. See a physician if irritation persists.

**Skin:** Wash with soap and water. See a physician if irritation persists. **Ingestion:** No harmful effects anticipated. See a physician if irritation persists. **Inhalation:** No harmful effects are anticipated. If a problem develops, remove the person to fresh air

and supply of oxygen if necessary.

#### **Section 7: Special Protection Information**

**Ventilation:** General mechanical and local exhaust in accordance with ACGIH recommendations. Protective Gloves: Wear gloves as a standard handling procedure.

**Eye Protection:** Dust-tight goggles are recommended during material abrading operations.

**Respiratory Protection:** Use NIOSH approved dust mask if required.

#### **Section 8: Special Precautions**

**Handling precautions:** Nuisance dust may be generated during some material machining processes.

#### **Section 9: Regulatory Information**

DOT-Proper shipping name: Plastic Laminate Sheets DOT Hazard Class: N/A RCRA Status: Not a hazardous waste under RCRA (40 CFR 261) SARA/TITLE III - Toxic chemicals list: This product does not contain a toxic chemical for routine annual toxic chemical release reporting under Sec. 313 (40 CFR 372)

Issued 1/11/98 by R. Snyder, Product Safety Director

### RAINIER RICHLITE COMPANY 624 E. 15<sup>th</sup> Street - Tacoma, WA 98421 888-383-5533



# RAINIER RICHLITE CO, INC. SKATELITE PRO FIVE YEAR LIMITED WARRANTY



RAINIER RICHLITE COMPANY warrants this product against defects in materials and workmanship for a period of five years from the date of original retail purchase (proof of purchase required). If RAINIER RICHLITE COMPANY receives notice of such defects during the warranty period, RAINIER RICHLITE COMPANY will either, at its option, repair or replace products that prove to be defective.

This Limited Warranty is applicable only to the original purchaser and may not be assigned or otherwise transferred.

Only merchandise that has been authorized for return by RAINIER RICHLITE COMPANY with a Return Material Order (RMO) number will be accepted for the consideration of issuance of appropriate credit or replacement.

Products of RAINIER RICHLITE COMPANY returned for warranty consideration must have return authorization and must be shipped prepaid to RAINIER RICHLITE COMPANY. RAINIER RICHLITE COMPANY will process all returns within a reasonable time and advise the Customer of the evaluation. Warranty consideration will follow RAINIER RICHLITE COMPANY'S written warranty for products prevailing at the time such product was purchased. All products found to be defective within the terms of the warranty will be repaired or replaced and returned to the Customer via surface freight prepaid by RAINIER RICHLITE COMPANY.

THERE IS NO OTHER WARRANTY, REPRESENTATION OR CONDITION OF ANY KIND; AND ANY WARRANTY, EXPRESS OR IMPLIED IS HEREBY EXCLUDED AND DISCLAIMED, INCLUDING THE IMPLIED WARRANTIES OR MERCHANTIBILITY AND OF FITNESS FOR A PARTICULAR PURPOSE.

IT IS UNDERSTOOD AND AGREED THAT SELLER'S LIABILITY AND PURCHASER'S SOLE REMEDY, WHETHER IN CONTRACT, UNDER ANY WARRANTY, IN TORT (INCLUDING NEGLIGENCE), IN STRICT LIABLITY OR OTHERWISE SHALL NOT EXCEED THE RETURN OF THE AMOUNT OF THE PURCHASED PRICE PAID BY PURCHASER, AND UNDER NO CIRCUMSTANCES SHALL SELLER BE LIABLE FOR



ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING, BUT NOT LIMITED TO, PERSONAL INJURY, PROPERTY DAMAGE, DAMAGE OR LOSS OF EQUIPMENT, LOST PRIFITS OR REVENUE, COST OF RENTING REPLACEMENTS AND OTHER ADDITIONAL EXPENSES, EVEN IF SELLER HAS BEEN ADVISED OF THE POSSIBLITY OF SUCH DAMAGES. THE PRICE STATED FOR THE EQUIPMENT IS A CONSIDERATION IN LIMITING SELLER'S LIABILITY AND PURCHASER'S REMEDY.

SELLER WIL NOT BE LIABLE FOR ANY DAMAGES, LOSSES OR EXPENSES AS A RESULT OF PURCHASER'S NEGLIGENCE, WHETHER DEEMED ACTIVE OR PASSIVE AND WHETHER OR NOT ANY SUCH NEGLIGENCE IS THE SOLE CAUSE OF ANY SUCH DAMAGE, LOSS OR EXPENSE.

This warranty gives you specific legal rights, and you may also have other rights, which may vary from state to state. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.